





# Mega paving slabs Carreau

## ► Maintenance

- Always clean the tiles immediately after a spill. Acidic products, animal droppings and vegetable residue can cause permanent stains.
- Remove normal contamination with a hard brush or a combination of a hard brush and clean water.
- For stubborn stains, we recommend a neutral detergent. For oil and grease stains, products are available at construction markets (Lösefix from Lithofin, HG Super remover ...).
- A green layer can usually be easily removed by treating the tiles (pouring or spraying) with anti-moss products. These are available at construction markets (Allex Lithofin).
- Avoid the use of a high-pressure cleaner, as this will damage the surface of the tiles and make them rougher. This will make the tiles more porous, which will result in them getting green and dirty faster.

## ► Placement

- Take precautions to prevent contamination during placement, cover with plastic if necessary – note: leaving the tiles covered for too long could cause efflorescence.
- Clean the surface with clean water every day at the end of the working day.
- Never do any sawing work on or next to the placed paving.
- Eliminate small imperfections and differences in thickness by tapping with a plastic hammer.
- For placement with a minimal joint, grouting is not necessary and even discouraged.
- For placement with a larger joint, rub it in with coarser grouting material such as clean crushed aggregates 1/3 or 2/5 mm. Never repoint with cement mortar to prevent freezing of joints.