

Concrete pavers Carreau+

The Carreau+ concrete pavers have a very sleek surface, are contemporary, dimensionally very stable, and can be laid with a minimal joint. This results in a tight-fitting contiguous, modern-looking surface. The 6 cm thick concrete pavers from the

Carreau+ range come in 13 colours and seven sizes (not every colour exists in every size). The multiformat Carreau+ Caprice provides opportunities to add beautiful accents to the creations.

► Colours



► Dimensions

| | GRIS NATUREL | ARDUNA | CARBON | NUANCE | MOCCA DUST | CEDAR DUST | TURF | MARBRE-GRIS | MARBRE-BRUN | BROWN-BLACK | RED-BLACK | AUTUMN | LATTE |
|--------------------------------------|--------------|--------|--------|--------|------------|------------|------|-------------|-------------|-------------|-----------|--------|-------|
| Non-aged (LxWxH) | | | | | | | | | | | | | |
| 40x30x6 cm | | ✓ | ✓ | | | | | | | | | | |
| 30x20x6 cm | ✓ | ✓ | ✓ | ✓ | | | ✓ | ✓ | ✓ | | | | ✓ |
| 30x10x6 cm | ✓ | ✓ | ✓ | | | | ✓ | | | | | | |
| 20x20x6 cm | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | | | ✓ |
| 20x5x6 cm | ✓ | ✓ | ✓ | ✓ | | | ✓ | | | | | | ✓ |
| 15x15x6 cm | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | | | | ✓ | ✓ | ✓ | ✓ |
| Caprice (7,5+15+22,5) x15x6 cm | | ✓ | | | | | | | | | | | |

Carreau Border (LxHxB)

| | | | | | | | | | | | | | |
|-------------|---|---|---|--|--|--|---|--|--|--|--|--|--|
| 100x20x6 cm | ✓ | ✓ | ✓ | | | | ✓ | | | | | | |
|-------------|---|---|---|--|--|--|---|--|--|--|--|--|--|



Concrete pavers Carreau+

► Maintenance

- Brush with clean water.
- For stubborn stains, we recommend a neutral detergent. For oil and grease stains, products are available at construction markets (Lösefix from Lithofin, HG Super remover ...).
- A green layer can usually be easily removed by treating the tiles (pouring or spraying) with anti-moss products. These are available at construction markets (Lithofin Allex, ...).
- Avoid the use of a high-pressure cleaner, as this will damage the surface of the tiles and make them rougher. This will make the tiles more porous, which will result in them getting green and dirty faster.
- After cleaning, spread sand in the joints.

► Placement

- Take precautions to prevent contamination during placement, cover with plastic if necessary – note: leaving the tiles covered for too long could cause efflorescence.
- Clean the surface with clean water every day at the end of the working day.
- Never do any sawing work on or next to the placed paving.
- Use a plate type compactor with adjustable vibration strength and fit the compactor with a clean rubber bottom.
- Avoid using the compactor in rainy weather conditions to prevent cement depositing on the surface.
- On top of the foundation, place a layer of packed sand of 3 or 4 cm thick, consisting of well graded, clean and washed river sand (0/5) with few fine particles.
- Fill up the joints with clean, white washed quartz sand. Using contaminated sand can lead to discolouration of the paving.

The Carreau+ is sensitive to wrong placement because of its completion without a bevelled edge, so please work carefully. Despite all precautions, this might result in a little damage. This is possible with a flat stone that is placed with a minimal joint and cannot give rise to complaints. Carreau+ pavers have a rough bottom and a smoother top. To prevent colour differences, always place the pavers with the smooth side on top.