

ALFRESCO


F L O O R S

Bentley 20mm

Precision External Non-Slip Porcelain Tiles

1	1	1
COLOURS	FINISHES	SIZES

- Bentley – inspiration drawn from natural, archetypal limestone
- Warm organic colour and natural anti-slip surface finish for high performance when wet
- A look that is both classic and contemporary to suit interior and exterior settings
- Also available in a 10mm thickness for indoor environments






Bynar

V3 - HIGH
SHADE VARIATION

PRINT COLOURS MAY VARY FROM ORIGINAL. TILE SAMPLES SHOULD BE REQUESTED

Breaking Strength	EN ISO 10545-4	S > 11000 N
Bending Strength	EN ISO 10545-4	R > 45 N/mm ²
Point Load	EN 12825	> 6 kN Centre > 7 kN Centre of Side > 4 kN Diagonal
Resistance to Abrasion	EN ISO 10545-6	< 120 mm ³

Important Note: for installations using pedestals that incorporate a void of 75mm or greater, please contact us for advice regarding the recommended provision of a reinforcing mesh for safety.



- A. Open Joint. Recommended spacer tab 3mm. Allows water to drain off the surface.
- B. Fully adjustable pedestal height: 40 – 1030mm. Option of built-in slope corrector to counteract undulating substrates and to accommodate drainage falls.

SIZE	FINISH	THICKNESS	COLOUR AVAILABILITY
1 595 x 595mm (R)	NATURAL ANTI-SLIP	20mm	ALL

(R) RECTIFIED SIZE / SQUARED EDGE WITH MICRO BEVEL

