

ALFRESCO

F L O O R S

Fresno

Precision External Non-Slip Porcelain Tiles

5

COLOURS

1

FINISHES

2

SIZES


- Fresno - design that evokes the beauty and style of natural stone
- A collection that takes inspiration from the natural world with exceptional technical standards
- Random blending of hues and shades for a truly stunning appearance
- Also available in 10mm thickness for a seamless combination for indoor and outdoor use




Feathertop




Finley



Fisher



Freel



Falla




PRINT COLOURS MAY VARY FROM ORIGINAL. TILE SAMPLES SHOULD BE REQUESTED

Breaking Strength	EN ISO 10545-4	S > 13000 N
Bending Strength	EN ISO 10545-4	R > 52 N/mm ²
Point Load	EN 12825	> 6 kN Centre > 7 kN Centre of Side > 4 kN Diagonal
Resistance to Abrasion	EN ISO 10545-6	< 150 mm ³

Important Note: for installations using pedestals that incorporate a void of 75mm or greater, please contact us for advice regarding the recommended provision of a reinforcing mesh for safety.

SIZE	FINISH	THICKNESS	COLOUR AVAILABILITY
1 1198 x 598mm (R)	NATURAL	20mm	02, 03 & 05
2 598 x 598mm (R)	NATURAL	20mm	ALL

(R) RECTIFIED SIZE / SQUARED EDGE WITH MICRO BEVEL.



- A. Open Joint. Recommended spacer tab 3mm. Allows water to drain off the surface.
- B. Fully adjustable pedestal height: 40 – 1030mm. Option of built-in slope corrector to counteract undulating substrates and to accommodate drainage falls.

