

Height Adjustment Range	12-18mm
Component Parts	1 x J1 (base, screw & head)
Head	Diameter Ø 150 mm The pedestal is supplied with 3 or 4mm spacer tabs for paving This head type features an integrated black rubber pad for noise protection & anti-slip
Base	Diameter Ø 150 mm Drainage holes Membrane friendly
Slope Correction	Self-levelling slope correction is included in the pedestal head as standard Up to 1.5% slope correction can be achieved
Laying Specifications	The pedestals do not require mechanical fixings or adhesives, & can be placed directly on top of the substrate
Field of Application	On any waterproofing membrane On any rigid insulation panel On any solid & compact laying surface
Raw Materials	20% Talc & 80% Polypropylene (100% recycled)
Environmental Impact	Recycled & reusable – non-hazardous materials
Warranty	25 years
Service Life	50 years
Origin	Designed & manufactured in Italy

J1

Up to 1.5% slope correction



1 x J1

Base



Ø 150 mm

Mechanical Tests - Compression testing after accelerated ageing

J1 with slope correction	4,176 N	425.9 KG
---------------------------------	----------------	-----------------

The compression tests carried out demonstrate that at the different loading conditions before & after the ageing cycles, there are no significant alterations of the material, the average values obtained are similar to the model used.

Chemical Tests

Chemical tests have shown that the material used (Polypropylene) has excellent physical resistance & dimensional stability.

- De-icing salts
- Pool water with chlorine
- Frost-defrost

