


Height Adjustment Range	21-30mm
Component Parts	1 x Q1 (screw & base) Head supplied separately
Head	Diameter Ø 130 mm Decking: requires Queen Joist Cradle Paving: requires Queen Head with Tabs – 2, 3 or 4mm. This head type features an integrated black rubber pad for noise protection & anti-slip
Base	Diameter Ø 205 mm Drainage holes Membrane friendly Pre-cut grooves for easy cutting if required
Slope Correction	Not included as standard The Queen Plus accessory provides up to 5% slope correction & adds 7mm to the height of the pedestal
Laying Specifications	The pedestals do not require mechanical fixings or adhesives, & can be placed directly on top of the substrate
Field of Application	On any waterproofing membrane On any rigid insulation panel On any solid & compact laying surface
Raw Materials	20% Talc & 80% Polypropylene (100% recycled)
Environmental Impact	Recycled & reusable – non-hazardous materials
Warranty	25 years
Service Life	50 years
Origin	Designed & manufactured in Italy

Q1



1 x Q1

Base



Ø 205 mm

Mechanical Tests - Compression testing after accelerated ageing

Q1 - Fixed	14,513.8 N	1,480.0 KG
Q1 & Queen Plus Slope Corrector	10,350.3 N	1,055.4 KG

Chemical Tests

Chemical tests have shown that the material used (Polypropylene) has excellent physical resistance & dimensional stability.

- De-icing salts
- Pool water with chlorine
- Frost-defrost

