


Height Adjustment Range	29-44mm
Component Parts	1 x Q2 (screw & base) Head supplied separately
Head	Diameter Ø 130 mm Decking: requires Queen Joist Cradle Paving: requires Queen Head with Tabs – 2, 3 or 4mm. This head type features an integrated black rubber pad for noise protection & anti-slip
Base	Diameter Ø 205 mm Drainage holes Membrane friendly Pre-cut grooves for easy cutting if required
Slope Correction	Not included as standard The Queen Plus accessory provides up to 5% slope correction & adds 7mm to the height of the pedestal
Laying Specifications	The pedestals do not require mechanical fixings or adhesives, & can be placed directly on top of the substrate
Field of Application	On any waterproofing membrane On any rigid insulation panel On any solid & compact laying surface
Raw Materials	20% Talc & 80% Polypropylene (100% recycled)
Environmental Impact	Recycled & reusable – non-hazardous materials
Warranty	25 years
Service Life	50 years
Origin	Designed & manufactured in Italy

Q2



1 x Q2

Base



Ø 205 mm

Mechanical Tests - Compression testing after accelerated ageing

Q2 - Fixed	13,998.3 N	1,427.4 KG
Q2 with Queen Plus - Tilting	10,227.0 N	1,042.9 KG

Chemical Tests

Chemical tests have shown that the material used (Polypropylene) has excellent physical resistance & dimensional stability.

- De-icing salts
- Pool water with chlorine
- Frost-defrost

